

DATA SHEET.

SCRUBBER DRYER

RA 55IK 40



columbus

PERFECT SUCTION. EXTREMELY ROBUST:
THE 40 LITRE CABLE MACHINE THAT GOES ON AND ON.
RA 55|K40



Practical: cleaning accessories always close at hand



Greater comfort with large wheels



Quick and easy seal changes



Perfect suction results even in tight turns



- The compact, mains operated scrubber dryer for continuous duty on small and medium size surfaces.
- Up close: the moulded, ergonomic operating handle and the single-axis design provide effortless manoeuvrability in the tightest space.
- Large wheels for greater comfort and easy transport.
- The mains operated machine is low in weight, making it the ideal solution for pressure sensitive floors.
- Large fresh water opening with mesh insert for rapid filling without the need to open the tank cover.
- Easy to clean: the recovery tank has smooth walls and opens fully for rinsing and disinfection. HACCP compliant.
- The cover seals can be changed quickly and easily without tools.
- Compact design and removable squeegee tool for easier handling and transport.
- Exceptionally high brush pressure for perfect cleaning results.
- Simple, intuitive operation with a self-explanatory display.
- The patented mounting system of the curved squeegee tool follows the movements of the machine and leaves no streaks even in tight turns.
- EUinted tested and certified.
- Made in Germany.

EUinted
Cleaning | European
Cleaning Machines
Association

RA 55|K40

L x W x H	1130 x 525 x 1055 mm
Working width	550 mm
Suction width	735 mm
Theoretical coverage max.	2200 m ² /h
Noise level	66 dB(A)
Empty weight	66 kg
Operating weight	106 kg

ELECTRICAL DATA

Rated voltage	230 V
Power max.	1600 W
Mains cable	25 m

TANK

Solution tank capacity	40 l
Recovery tank capacity	45 l

SUCTION

Low pressure max.	204 mbar
Air flow max.	45 l/s

BRUSHES AND PAD HOLDERS

Number	1
Speed	150 U/min
Brush pressure	37 kg