

DATA SHEET.

## INDUSTRIAL VACUUM.

IWV 80



G. Staehle GmbH u. Co. KG  
Mercedesstraße 15  
D 70372 Stuttgart  
Telefon +49 (0) 7 11/95 44-950  
Telefax +49 (0) 7 11/95 44-941  
info@columbus-clean.com  
www.columbus-clean.com

**columbus**

# FOR ALL LIQUIDS:

## IWV 80

- Compact wet vacuum for many industrial applications.
- Controlled emptying with drain hose.
- Made of robust, epoxy-coated steel. Non-marking rollers and locking brake for safety and comfort while emptying.
- Safety cut-out when the container is full.
- Two individually switchable bypass suction motors.



### Bypass motors

With the bypass motor, the suction air flow is not also used to cool the motor. The motor is cooled with a separate air flow. This stops the motor overheating when cleaning hot dusts for example.

**Applications:**  
For various wet applications in  
virtually all industrial sectors



Drain hose from container



Accessories kit for IWV 80



Optional rubber suction tool



Effective removal of liquids with  
the floor tool

| IWV 80              |                    |
|---------------------|--------------------|
| L x B x H           | 530x660x1080 mm mm |
| Tool connection     | 80 mm              |
| PVC hose            | PVC 3 m/50 mm      |
| Container volume    | 80 l               |
| Filter surface area | -                  |
| Filter type         | Polyester catridge |
| Filter dust class   | -                  |

**ELECTRICAL DATA**

|                    |        |
|--------------------|--------|
| Rated voltage      | 230 V  |
| Rated power, total | 2,3 KW |
| Mains cable        | 10 m   |

**SUCTION MOTOR**

|                         |                          |
|-------------------------|--------------------------|
| Negative pressure, max. | 2500 mm.H <sub>2</sub> O |
| Air flow, max.          | 360 M <sup>3</sup> /h    |
| Number of motors        | 2                        |